



VIMEK 630 MINIMASTER

VIMEK[®]



VIMEK 630 MINIMASTER: The new generation Minimaster, 8-wheel driven mini-forwarder now has frame and servo steering and wide tyres. 2-level joystick is available as option. Ground clearance of almost 40 cm and a smooth underside, protects all the vulnerable parts – a machine for extreme situations. Vimek 630 Minimaster can be combined with several options and accessories for different needs! This makes it very manoeuvrable.



TECHNICAL SPECIFICATION VIMEK 630 MINIMASTER

Engine: Honda 630 cc

Fuel tank: 14 liters

Gear box: High, low, reverse

Transmission: Variable mechanical

Speed: 0 – 25 km/hour

Tires: 27 x 11 x 14

Weight tractor: 524 kg

Weight incl. crane and trailer: 1 200 kg

Ground clearness: 38 cm

Length: 2,08 m

Width: 1,15 m

Height: 2,35 m

Servo steering: Hydraulic Orbitrol

Rear axle: Oscillation +/- 30°

Hydraulic: 20 l/min 175 bar

Crane: Vimek 362

- Max reach, 3,60 m
- Turning angle, 210°
- Rotator, continues rotation
- Gripping area, 0,15 m²
- Weight incl. stabilizers and protection guard, 341 kg

Driven trailer:

- Robson drive between boogie wheels
- Capstan between wheels
- Loading capacity, 2 000 kg
- Loading area, 0,8 m²

Extra accessories:

- Wheel tracks
- Winch frame
- Radio controlled hydraulic winch
- Frame for hydraulic valves and lights
- Working lights LED
- Crane damping system
- Snow blade
- Bucket attachment (Clam shell bucket)
- Holder for chain saw
- 2-level joystick
- Frame steering

VIMEK®

For more information and to find your nearest retailer, please visit our website
www.vimek.se